

Serial No.: 10/023,457

Docket No.: KCC-16588

**Listing of Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Previously presented) A disposable garment comprising:  
at least one front panel comprising a fastening component;  
at least one back panel comprising a mating fastening component;  
at least one frangible bond connecting the front panel and the back panel,  
the fastening component and the mating fastening component being in the unfastened condition;  
  
wherein the at least one frangible bond is located outward of the fastening component and the mating fastening component.
2. (Original) The disposable garment of Claim 1, further comprising at least one first opening and at least one second opening.
3. (Original) The disposable garment of Claim 2 wherein the frangible bond extends substantially from the first opening to the second opening.
4. (Original) The disposable garment of Claim 2 wherein the frangible bond extends a partial distance from the first opening to the second opening.

KCC-2123

2

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

5. (Original) The disposable garment of Claim 1 wherein the frangible bond has a width in a range from about 1 mm to about 25 mm.

6. (Original) The disposable garment of Claim 1 wherein the frangible bond has a width in a range from about 2 mm to about 10 mm.

7. (Original) The disposable garment of Claim 1 wherein the frangible bond has a width in a range from about 3 mm to about 6 mm.

8. (Original) The disposable garment of Claim 1 wherein a strength of the frangible bond is in a range from about 10 grams to about 2700 grams.

9. (Original) The disposable garment of Claim 1 wherein a strength of the frangible bond is less than about 2700 g.

10. (Original) The disposable garment of Claim 1 wherein a strength of the frangible bond is in a range from about 200 grams to about 2000 grams.

11. (Original) The disposable garment of Claim 1 wherein a strength of the frangible bond is less than about 2000 g.

12. (Original) The disposable garment of Claim 1 wherein a strength of the frangible bond is in a range from about 500 grams to about 1000 grams.

KCC-2123

3

MMCI

Serial No.: 10/023,457

Docket No.: KCC-16588

13. (Original) The disposable garment of Claim 1 wherein a strength of the frangible bond is less than about 1000 g.

14. (Original) The disposable garment of Claim 1 wherein the frangible bond is located on a tab which extends from one of the front panel and the back panel.

15-18. (Canceled)

KCC-2123

4

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

19. (Previously presented) An absorbent garment, comprising:

a chassis including a first front side panel and a second front side panel, a first back side panel and a second back side panel, and defining a waist opening and first and second leg openings;

each front side panel having an inner surface and an outer surface and defining a distal edge;

each back side panel having an inner surface and an outer surface and defining a distal edge;

a first frangible bond connecting the first front side panel and the first back side panel;

a second frangible bond connecting the second front side panel and the second back side panel;

wherein each of the front side panels comprises a fastening component bonded to one of the inner and the outer surfaces adjacent the distal edge of the front side panel, and each of the back side panels comprises a mating fastening component bonded to one of the inner and the outer surfaces adjacent the distal edge of the back side panel, the fastening component and the mating fastening component being in the unfastened condition;

wherein each of the front side panels defines a distance between the fastening component and the distal edge, and each of the back side panels defines a distance between the mating fastening component and the distal edge; and

wherein each frangible bond is located outward of each fastening component and each mating fastening component.

KCC-2123

5

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

20. (Original) The absorbent garment of Claim 19 wherein the first frangible bond extends substantially from the waist opening to the first leg opening, and the second frangible bond extends substantially from the waist opening to the second leg opening.

21. (Original) The absorbent garment of Claim 19 wherein the first frangible bond extends a partial distance from the waist opening to the first leg opening, and the second frangible bond extends a partial distance from the waist opening to the second leg opening.

22. (Original) The absorbent garment of Claim 19 wherein the distance between each of the fastening components and the distal edge of one of the front side panels is in a range from about 1 mm to about 25 mm.

23. (Original) The absorbent garment of Claim 19 wherein the distance between each of the mating fastening components and the distal edge of one of the back side panels is in a range from about 1 mm to about 25 mm.

24. (Original) The absorbent garment of Claim 19 wherein the distance between each of the fastening components and the distal edge of one of the front side panels is in a range from about 2 mm to about 10 mm.

KCC-2123

6

MMC/

Serial No.: 10/023,457

Docket No.: KCC-16588

25. (Original) The absorbent garment of Claim 19 wherein the distance between each of the mating fastening components and the distal edge of one of the back side panels is in a range from about 2 mm to about 10 mm.

26. (Original) The absorbent garment of Claim 19 wherein the distance between each of the fastening components and the distal edge of one of the front side panels is in a range from about 3 mm to about 6 mm.

27. (Original) The absorbent garment of Claim 19 wherein the distance between each of the mating fastening components and the distal edge of one of the back side panels is in a range from about 3 mm to about 6 mm.

28. (Original) The absorbent garment of Claim 19 wherein each of the first and second frangible bonds have a width in a range from about 1 mm to about 25 mm.

29. (Original) The absorbent garment of Claim 19 wherein a strength of each of the frangible bonds is less than about 2700 grams.

30. (Original) The absorbent garment of Claim 19 wherein a strength of each of the frangible bonds is less than about 2000 grams.

KCC-2123

7

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

31. (Original) The absorbent garment of Claim 19 wherein a strength of each of the frangible bonds is in a range from about 500 grams to about 1000 grams.

32. (Original) The absorbent garment of Claim 19 wherein each of the first and second frangible bonds is located on at least one tab which extends from the distal edge of at least one of the side panels.

33-35. (Canceled)

KCC-2123

8

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

36. (Previously presented) An absorbent garment, comprising:

a chassis including a first front side panel and a second front side panel, a first back side panel and a second back side panel, defining a waist opening and first and second leg openings, and each front side panel and each back side panel having an inner surface and an outer surface;

each front side panel defining a distal edge;

each back side panel defining a distal edge;

a first frangible bond connecting the first front side panel and the first back side panel; and

a second frangible bond connecting the second front side panel and the second back side panel;

each front side panel and each back side panel having a nonwoven substrate and at least one of the front side panels and the back side panels defining an attachment surface; and

at least one fastening component bonded to one of the front side panels and the back side panels on one of the inner surface and the outer surface, the at least one fastening component comprising a mechanical fastening element adapted to refastenably engage the attachment surface, the mechanical fastening element and the attachment surface being in the unfastened condition;

wherein each frangible bond is located outward of each mechanical fastening element.

KCC-2123

9

MMC/I



Serial No.: 10/023,457

Docket No.: KCC-16588

37. (Original) The absorbent garment of Claim 36 wherein the at least one fastening component is bonded to the inner surface of the chassis.

38. (Original) The absorbent garment of Claim 36 wherein the at least one fastening component is bonded to the outer surface of the chassis.

39. (Original) The absorbent garment of Claim 36 wherein the attachment surface comprises complementary loop fasteners.

40. (Original) The absorbent garment of Claim 36 wherein the attachment surface comprises complementary hook fasteners.

41-43. (Canceled)

44. (Original) The absorbent garment of Claim 36 wherein each of the first and second frangible bonds have a width in a range from about 1 mm to about 25 mm.

45. (Original) The absorbent garment of Claim 36 wherein each of the first and second frangible bonds have a width in a range from about 2 mm to about 10 mm.

46. (Original) The absorbent garment of Claim 36 wherein a strength of each of the frangible bonds is less than about 2700 grams.

KCC-2123

10

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

47. (Original) The absorbent garment of Claim 36 wherein a strength of each of the frangible bonds is less than about 2000 grams.

48. (Original) The absorbent garment of Claim 36 wherein a strength of each of the frangible bonds is in a range from about 500 grams to about 1000 grams.

KCC-2123

11

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

49. (Previously presented) An absorbent garment, comprising:

a chassis including a first front side panel and a second front side panel, a first back side panel and a second back side panel, defining a waist opening and first and second leg openings, and each front side panel and each back side panel having an inner surface and an outer surface;

each front side panel defining a distal edge;

each back side panel defining a distal edge;

a first frangible bond connecting the first front side panel and the first back side panel; and

a second frangible bond connecting the second front side panel and the second back side panel;

each front side panel and each back side panel having a nonwoven substrate and at least one of the front side panels and the back side panels defining an attachment surface; and

at least one fastening component bonded to one of the front side panels and the back side panels on one of the inner surface and the outer surface, the at least one fastening component comprising a mechanical fastening element adapted to refastenably engage the attachment surface, the mechanical fastening element and the attachment surface being in the unfastened condition wherein one of each front side panel and each back side panel further comprises a perforation.

KCC-2123

12

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

50. (Original) The absorbent garment of Claim 49 wherein each perforation is located inward of each frangible bond.

51. (Original) The absorbent garment of Claim 49 wherein each perforation is located outward of the each frangible bond.

KCC-2123

13

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

52. (Previously presented) An absorbent garment, comprising:

a chassis including a first front side panel and a second front side panel, a first back side panel and a second back side panel, defining a waist opening and first and second leg openings, and each front side panel and each back side panel having an inner surface and an outer surface;

each front side panel defining a distal edge;

each back side panel defining a distal edge;

a first frangible bond connecting the first front side panel and the first back side panel; and

a second frangible bond connecting the second front side panel and the second back side panel;

a portion of the chassis having a nonwoven substrate defining an attachment surface; and

at least one fastening component bonded to one of the front side panels and the back side panels on one of the inner surface and the outer surface, the at least one fastening component comprising a mechanical fastening element adapted to refastenably engage the attachment surface, the mechanical fastening element and the attachment surface being in the unfastened condition;

wherein each frangible bond is located outward of each mechanical fastening element.

KCC-2123

14

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

53-55. (Canceled)

56. (Original) The absorbent garment of Claim 52 wherein a strength of each of the frangible bonds is less than about 2700 grams.

57. (Original) The absorbent garment of Claim 52 wherein a strength of each of the frangible bonds is less than about 2000 grams.

58. (Canceled)

KCC-2123

15

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

59. (Previously Presented) An absorbent garment, comprising:

a chassis including a first front side panel and a second front side panel, a first back side panel and a second back side panel, and each front side panel and each back side panel having an inner surface and an outer surface;

one of the front side panels and the back side panels comprising a nonwoven substrate and defining an attachment surface; and

at least one fastening component bonded to the inner surface of one of the front side panels and the back side panels, the at least one fastening component comprising a mechanical fastening element adapted to refastenably engage the attachment surface;

wherein the at least one fastening component engages the attachment surface, and the inner surface of the first front side panel faces the inner surface of the first back side panel;

wherein the attachment surface is located on the inner surface and the outer surface of one of the front side panels and the back side panels.

KCC-2123

16

MMC/I

Serial No.: 10/023,457

Docket No.: KCC-16588

60. (Previously presented) A disposable refastenable garment comprising:  
at least one front panel comprising a fastening component;  
at least one back panel comprising a mating fastening component;  
at least one frangible bond connecting the front panel and the back panel,  
the fastening component and the mating fastening component being in the unfastened  
condition;

wherein the at least one frangible bond is aligned with the fastening  
component and the mating fastening component.

KCC-2123

17

MMC/I